

# **CLOSED VERTICAL CYLINDRICAL TANK**BOT TYPE STORAGE

POLYETHYLENE (PE)



Redonnons le meilleur à la terre

2394

#### 1 Technical definition

One-piece rotationally molded tank in food-grade, linear, high-density polyethylene, UV-protected

- Cylindrical shape, with flat bottom and screw-on lid on top of the tank
- Designed for storage of all food and chemical products (check compatibility) as well as drinking water (see ACS range)
- Graduation to determine content level. (except BOT12000\*\*\* and ACS models)









## 2 Advantages

- One-piece moulded tank, with no glue or welds, so perfectly leakproof
- Excellent impact resistance
- Smooth inner surface prevents sedimentation and facilitates cleaning.
- Eccentric top screw-on lid for easy tank filling.
- Flat part at the bottom to place a tank outlet
- ACS range (Certificate of sanitary compliance)

### 3 Use

- BOT tanks are designed for the storage of drinking water (ACS), liquid fertilizers and food products, etc
- For chemical products, please consult our sales department for compatibility tables




Above-ground tanks cannot be buried.

## 4 Valves\*



| Valves | Designation                    |
|--------|--------------------------------|
| VPP40  | Ball valve + wall bushing DN40 |
| VPP50  | Ball valve + wall bushing DN50 |



| REFERENCES  |                        | USEFUL VOLUME |      |      |           |        | Mounted valve |
|-------------|------------------------|---------------|------|------|-----------|--------|---------------|
| NO ACS*     | ACS** (FRENCH<br>ONLY) | (L)           | Ø    | A    | Ø OPENING | WEIGHT | reference     |
| BOT2000     | ACS BOT2000            | 2000          | 1400 | 1550 | 385       | 60     | VPP40         |
| BOT3000     | ACS BOT3000            | 3000          | 1520 | 1900 | 385       | 100    |               |
| -           | ACS BOT4000            | 4000          | 1900 | 1860 | 385       | 120    |               |
| BOT5000     | ACS BOT5000            | 5000          | 1900 | 2250 | 385       | 150    |               |
| -           | ACS BOT5500            | 5500          | 2400 | 1440 | 385       | 150    |               |
| -           | ACS BOT6500            | 6500          | 2400 | 1675 | 385       | 195    | VPP50         |
| -           | ACS BOT7500            | 7500          | 2400 | 1910 | 385       | 225    |               |
| -           | ACS BOT8500            | 8500          | 2400 | 2130 | 385       | 155    |               |
| -           | ACS BOT10500           | 10500         | 2400 | 2595 | 385       | 315    |               |
| BOT12000*** | ACS BOT12000           | 12000         | 2400 | 2948 | 385       | 340    |               |

- \* Please note that valves are optional for the non-ACS range
- \*\* ACS tanks are blue
- \*\*\* BOT12000 models are black